

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.07.2022

Version number 2 (replaces version 1)

Revision: 07.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **Epoxy-Remover**
- Article number: 11983
- UFI: P7J6-60HQ-900Q-KPSU

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Paint remover

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg
- Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS05 GHS07

Signal word

Danger

Hazard-determining components of labelling:

2-aminoethanol
potassium hydroxide

Hazard statements

H314 Causes severe skin burns and eye damage.
H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P260 Do not breathe mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

(Contd. on page 2)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.07.2022

Version number 2 (replaces version 1)

Revision: 07.07.2022

Trade name: Epoxy-Remover

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**· 3.2 Mixtures**

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

141-43-5	2-aminoethanol Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335 Aquatic Chronic 3, H412 Specific concentration limit: STOT SE 3; H335: C ≥ 5 %	<10%
1310-58-3	potassium hydroxide Met. Corr. 1, H290; Skin Corr. 1A, H314; Eye Dam. 1, H318 Acute Tox. 4, H302 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 5 % Skin Corr. 1B; H314: 2 % ≤ C < 5 % Skin Irrit. 2; H315: 0.5 % ≤ C < 2 % Eye Irrit. 2; H319: 0.5 % ≤ C < 2 %	<10%
112-34-5	2-(2-butoxyethoxy)ethanol Eye Irrit. 2, H319	1-5%
122-99-6	2-Phenoxyethanol Acute Tox. 4, H302; Eye Irrit. 2, H319	1-5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**· 4.1 Description of first aid measures**

· General information: Immediately remove any clothing soiled by the product.

· After inhalation: In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

· Hazards: No further relevant information available.

Danger of impaired breathing.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.07.2022

Version number 2 (replaces version 1)

Revision: 07.07.2022

Trade name: Epoxy-Remover

(Contd. of page 2)

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

· **5.3 Advice for firefighters**

· Protective equipment:

Wear self-contained respiratory protective device.
Wear fully protective suit.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**

· Storage:

· Requirements to be met by storerooms and receptacles:

No special requirements.

· Information about storage in one common storage facility:

Not required.

· Further information about storage conditions:

Protect from frost.

Keep container tightly sealed.

· Storage class:

8 A

· **7.3 Specific end use(s)**

No further relevant information available.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.07.2022

Version number 2 (replaces version 1)

Revision: 07.07.2022

Trade name: Epoxy-Remover

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**· Ingredients with limit values that require monitoring at the workplace:**141-43-5 2-aminoethanol**

IOELV	Short-term value: 7.6 mg/m ³ , 3 ppm Long-term value: 2.5 mg/m ³ , 1 ppm Skin
-------	---

112-34-5 2-(2-butoxyethoxy)ethanol

IOELV	Short-term value: 101.2 mg/m ³ , 15 ppm Long-term value: 67.5 mg/m ³ , 10 ppm
-------	--

· DNELs**141-43-5 2-aminoethanol**

Oral	DNEL (Langzeit-wiederholt)	3.75 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	1 mg/kg bw/day (ARB) 0.24 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	3.3 mg/m ³ Air (ARB) 2 mg/m ³ Air (BEV)

1310-58-3 potassium hydroxide

Inhalative	DNEL (Langzeit-wiederholt)	1 mg/m ³ Air (ARB) 1 mg/m ³ Air (BEV)
------------	----------------------------	--

112-34-5 2-(2-butoxyethoxy)ethanol

Oral	DNEL (Langzeit-wiederholt)	5 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	83 mg/kg bw/day (ARB) 50 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	101.2 mg/m ³ Air (ARB) 7.5 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	67.5 mg/m ³ Air (ARB) 40.5 mg/m ³ Air (BEV)

122-99-6 2-Phenoxyethanol

Oral	DNEL (Langzeit-wiederholt)	17.43 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	34.72 mg/kg bw/day (ARB) 20.83 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	2.5 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	8.07 mg/m ³ Air (ARB) 2.5 mg/m ³ Air (BEV)

· PNECs**141-43-5 2-aminoethanol**

PNEC (wässrig)	100 mg/l (KA) 0.0085 mg/l (MW) 0.085 mg/l (SW) 0.028 mg/l (WAS)
PNEC (fest)	0.035 mg/kg Trockengew (BO) 0.043 mg/kg Trockengew (MWS) 0.434 mg/kg Trockengew (SWS)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.07.2022

Version number 2 (replaces version 1)

Revision: 07.07.2022

Trade name: Epoxy-Remover

(Contd. of page 4)

112-34-5 2-(2-butoxyethoxy)ethanol

PNEC (wässrig)	200 mg/l (KA)
	0.1 mg/l (MW)
	1 mg/l (SW)
	3.9 mg/l (WAS)
PNEC (fest)	0.32 mg/kg Trockengew (BO)
	0.44 mg/kg Trockengew (MWS)
	4.4 mg/kg Trockengew (SWS)

122-99-6 2-Phenoxyethanol

PNEC (wässrig)	24.8 mg/l (KA)
	0.0943 mg/l (MW)
	0.943 mg/l (SW)
	3.44 mg/l (WAS)
PNEC (fest)	1.26 mg/kg Trockengew (BO)
	0.7237 mg/kg Trockengew (MWS)
	7.2366 mg/kg Trockengew (SWS)

· Additional information:

The lists valid during the making were used as basis.

· **8.2 Exposure controls**· Appropriate engineering controls

No further data; see item 7.

· Individual protection measures, such as personal protective equipment· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the eyes and skin.
 Do not eat, drink, smoke or sniff while working.
 Use skin protection cream for skin protection.
 Clean skin thoroughly immediately after handling the product.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.
 Filter AX

· Hand protection

Preventive skin protection by use of skin-protecting agents is recommended.
 After use of gloves apply skin-cleaning agents and skin cosmetics.
 Skin protection agent recommendation for preventive skin shelter without use of protective gloves:
 STOKODERM (<http://www.stoko.com>)
 Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:
 STOKO EMULSION (<http://www.stoko.com>)
 Skin protection recommendation for skin cleaning after product handling:
 FRAPANTOL (<http://www.stoko.com>)
 Skin protection agent recommendation for skin aftercare:
 STOKO VITAN (<http://www.stoko.com>)
 The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.
 This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.07.2022

Version number 2 (replaces version 1)

Revision: 07.07.2022

Trade name: Epoxy-Remover

(Contd. of page 5)

protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Value for the permeation: Level \leq 6, 480 min

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Butoject (KCL, Art_No. 897, 898)

· As protection from splashes gloves made of the following materials are suitable:

Chloroprene rubber, CR

Camapren (KCL, Art_No. 720, 722, 726)

Fluorocarbon rubber (Viton)

Vitoject (KCL, Art_No. 890)

· Not suitable are gloves made of the following materials:

Nitrile rubber, NBR

· Eye/face protection**Tightly sealed goggles**· Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**· General Information· Colour:

Yellowish

· Odour:

Light

· Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling range

100 °C (7732-18-5 water, distilled, conductivity or of similarpurity)

· Lower and upper explosion limit· Lower:

1.3 Vol %

· Upper:

9.5 Vol %

· Flash point:

93 °C (141-43-5 2-aminoethanol)

· Ignition temperature:

385 °C (141-43-5 2-aminoethanol)

· pH at 20 °C

14

· Viscosity:· Kinematic viscosity

Not determined.

· Dynamic:

Not determined.

· Solubility· water:

Fully miscible.

· Vapour pressure:

Not determined.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.07.2022

Version number 2 (replaces version 1)

Revision: 07.07.2022

Trade name: Epoxy-Remover

(Contd. of page 6)

· Density and/or relative density
 · Density at 20 °C: 1.06 g/cm³

· 9.2 Other information

· Appearance:
 · Form: Fluid
 · Important information on protection of health and environment, and on safety.
 · Auto-ignition temperature: Product is not selfigniting.
 · Explosive properties: Product does not present an explosion hazard.
 · Solvent content:
 · Organic solvents: 18.5 %
 · Water: 69.9 %
 · Solids content: 9.7 %

· Information with regard to physical hazard classes

· Explosives Void

· Flammable gases Void

· Aerosols Void

· Oxidising gases Void

· Gases under pressure Void

· Flammable liquids Void

· Flammable solids Void

· Self-reactive substances and mixtures Void

· Pyrophoric liquids Void

· Pyrophoric solids Void

· Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable gases in contact with water Void

· Oxidising liquids Void

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.07.2022

Version number 2 (replaces version 1)

Revision: 07.07.2022

Trade name: Epoxy-Remover

(Contd. of page 7)

· <u>Oxidising solids</u>	Void
· <u>Organic peroxides</u>	Void
· <u>Corrosive to metals</u>	Void
· <u>Desensitised explosives</u>	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
· 10.3 Possibility of hazardous reactions	Reacts with strong acids and oxidising agents.
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	No further relevant information available.
· 10.6 Hazardous decomposition products:	Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008	
· <u>Acute toxicity</u>	Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	>2,322-3,385 mg/kg (rat)
Dermal	LD50	12,639 mg/kg (rbt)
Inhalative	LC50/4 h	136 mg/l

141-43-5 2-aminoethanol

Oral	LD50	1,089 mg/kg (rat)
Dermal	LD50	1,025 mg/kg (rbt)
Inhalative	LC50/4h	1,487 mg/m ³ (rat)
	LC50/4 h	11 mg/l (ATE)

1310-58-3 potassium hydroxide

Oral	LD50	363 mg/kg (rat)
------	------	-----------------

112-34-5 2-(2-butoxyethoxy)ethanol

Oral	LD50	2,410 mg/kg (mouse)
		>2,000 mg/kg (rat)
Dermal	LD50	2,764 mg/kg (rbt)

122-99-6 2-Phenoxyethanol

Oral	LD50	>300-2,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)

· <u>Skin corrosion/irritation</u>	Causes severe skin burns and eye damage.
· <u>Serious eye damage/irritation</u>	Causes serious eye damage.
· <u>Respiratory or skin sensitisation</u>	Based on available data, the classification criteria are not met.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.07.2022

Version number 2 (replaces version 1)

Revision: 07.07.2022

Trade name: Epoxy-Remover

(Contd. of page 8)

- | | |
|--------------------------|---|
| · Germ cell mutagenicity | Based on available data, the classification criteria are not met. |
| · Carcinogenicity | Based on available data, the classification criteria are not met. |
| · Reproductive toxicity | Based on available data, the classification criteria are not met. |
| · STOT-single exposure | May cause respiratory irritation. |
| · STOT-repeated exposure | Based on available data, the classification criteria are not met. |
| · Aspiration hazard | Based on available data, the classification criteria are not met. |

· 11.2 Information on other hazards

- | |
|-----------------------------------|
| · Endocrine disrupting properties |
|-----------------------------------|

None of the ingredients is listed.

SECTION 12: Ecological information**· 12.1 Toxicity**

- | |
|---------------------|
| · Aquatic toxicity: |
|---------------------|

141-43-5 2-aminoethanol

EC50	>1,000 mg/l (BES) (OECD 209)
	110 mg/l (pseudomonas putida)
EC10/18h	87 mg/l (pseudomonas putida)
EC50/48h	65 mg/l (daphnia magna) (67/548/EWG, Anhang V, C.2.)
EC50/16h	110 mg/l (pseudomonas putida) (DIN 38412)
EC20/0.5h	>1,000 mg/l (BES) (OECD 209)
NOEC/21d	0.85 mg/l (daphnia magna)
EC50/72h	22 mg/l (Scenedesmus subspicatus) (EG 92/69)
	2.5 mg/l (selenastrum capricornutum) (OECD 201)
LC50/96h	170 mg/l (carassius auratus) (APHA 1971)
	349 mg/l (Cyprinus carpio) (OECD 203; 92/69 EG)
	329 mg/l (lem)

1310-58-3 potassium hydroxide

LC50/24h	165 mg/l (Guppy)
EC50/15min	22 mg/l (Phosphobakteriumphosphoreum)
EC50/48h	40.4 mg/l (daphnia magna)
LC50/96h	80 mg/l (Mosquitofisch)
	45.4 mg/l (rainbow trout)

112-34-5 2-(2-butoxyethoxy)ethanol

EC50/24h	2,850 mg/l (daphnia magna) (DIN 38412)
EC50/96h	>100 mg/l (Desmodesmus subspicatus)
	>100 mg/l (Scenedesmus subspicatus)
EC10/16h	1,170 mg/l (pseudomonas putida)
EC5	73 mg/l (Entosiphon sulcatum)
EC50/48h	>100 mg/l (daphnia magna)
NOEC	>100 mg/kg (Desmodesmus subspicatus)
EC10	>1,995 mg/l (Klärschlamm: Atmungs-/Vermehrungshemmung)
EC50/72h	>100 mg/l (Desmodesmus subspicatus)
LC50/96h	1,300 mg/l (Iepomis macrochirus)
	>100 mg/l (Leuciscus idus)
	1,150 mg/l (poecilia reticulata)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.07.2022

Version number 2 (replaces version 1)

Revision: 07.07.2022

Trade name: Epoxy-Remover

(Contd. of page 9)

122-99-6 2-Phenoxyethanol

EC50/48h	>100 mg/l (daphnia magna)
NOEC	>1 mg/kg (pimephales promelas)
NOEC/21d	>1 mg/l (daphnia magna)
EC10	>100 mg/l (pseudomonas putida)
EC50/72h	>100 mg/l (Scenedesmus subspicatus)
LC50/96h	>100 mg/l (pimephales promelas)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· PBT:

Not applicable.

· vPvB:

Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· Additional ecological information:

· General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 13*	solvents

· Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· ADR, IMDG, IATA

UN1719

· **14.2 UN proper shipping name**

· ADR

1719 CAUSTIC ALKALI LIQUID, N.O.S. (POTASSIUM HYDROXIDE)

· IMDG, IATA

CAUSTIC ALKALI LIQUID, N.O.S. (POTASSIUM HYDROXIDE)

(Contd. on page 11)

EU

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.07.2022

Version number 2 (replaces version 1)

Revision: 07.07.2022

Trade name: Epoxy-Remover

(Contd. of page 10)

· 14.3 Transport hazard class(es)· ADR· Class

8 (C5) Corrosive substances.

· Label

8

· IMDG, IATA· Class

8 Corrosive substances.

· Label

8

· 14.4 Packing group· ADR, IMDG, IATA

II

· 14.5 Environmental hazards:· Marine pollutant:

No

· 14.6 Special precautions for user· Hazard identification number (Kemler code):

80

· EMS Number:

F-A,S-B

· Segregation groups

(SGG18) Alkalis

· Stowage Category

A

· Segregation Code

SG22 Stow "away from" ammonium salts

SG35 Stow "separated from" SGG1-acids

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:· ADR· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category

2

· Tunnel restriction code

E

· IMDG· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 1719 CAUSTIC ALKALI LIQUID, N.O.S. (POTASSIUM HYDROXIDE), 8, II

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.07.2022

Version number 2 (replaces version 1)

Revision: 07.07.2022

Trade name: Epoxy-Remover

(Contd. of page 11)

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 55

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 758.4 g/l

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Laboratory
- Contact: Elke Hake
Fon ++49 (0)911 64296-59
@mail E.Hake@akemi.de
- Date of previous version: 07.07.2022

· Version number of previous version: 1

- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.07.2022

Version number 2 (replaces version 1)

Revision: 07.07.2022

Trade name: Epoxy-Remover

(Contd. of page 12)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Met. Corr. 1: Corrosive to metals – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

EU