111

HAND-CUT STENCIL

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

Hand-cut, high quality, durable stencil coated with an advanced medium tack, rubber-based pressure-sensitive adhesive protected by an easy-release-treated HDPE liner. Designed for superior shape carving in marble and granite. Unique rubber formula allows easy cutting with less frequent knife sharpening. Controlled shrinkage gives accurate panel replacement after frosting. Recommended for maximum depth glass etching.

PRODUCT APPLICATIONS

For optimum performance, use with #211 Stencil Filler.

STANDARD SIZES:

12.75" x 10 yards 18.75" x 10 yards 21" x 10 yards 25" x 10 yards 30" x 10 yards 30.50" x 10 yards

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive Medium Tack / Rubber

Total Thickness (mils) 48 (1.22mm)

PSTC-133

Tensile Strength (lbs/in) 5 (21.9 N/25mm)

PSTC-131

180° Adhesion to Steel (oz/in) 17.5 (4.8 N/25mm)

PSTC-101

Elongation (% at break) 300

PSTC-131





100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 07/15

