

# 1258

## SINGLE LINER HIGH TACK MEDIA BLAST STENCIL - HAND CUT

### DESCRIPTION

Hand-cut, high quality, durable stencil coated with an advanced, high tack, water-based, pressure-sensitive, acrylic adhesive protected by an easy-release, 2mil clear PET liner. #1258 is designed and recommended for raw/unfinished wood, HDU foam-board, brick and rough stone.

### PRODUCT APPLICATION

For best results on marble, granite or polished surfaces, it is recommended to remove the tape immediately after sandblasting process. Recommended use with 333 Filler.

### STANDARD SIZES:

12.5", 18.75", 25" x 10 yards



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 09/20

## INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Adhesive</b>	Acrylic
<b>Total Thickness</b> (mil) PSTC-133	40.4 (1.04mm)
<b>Tensile Strength</b> (lbs/in) PSTC-131	4 (17.5 N/25mm)
<b>180° Adhesion to Steel</b> (oz/in) PSTC-101	42.5 (11.62 N/25mm)
<b>Elongation</b> (% at break) PSTC-131	500



**ANCHOR**  
brand stencil products