

153

SINGLE LINER HOLELESS STENCIL FOR FRICTION-FED CUTTERS

DESCRIPTION

High quality, durable, stencil coated with an advanced medium tack, rubber-based, pressure-sensitive adhesive protected by a clear polyester liner. Un-punched for friction-fed cutters and is designed for use on primed/painted wood and HDU foam-board. #153 is the friction-feed option for double-process shaped carving on polished marble or granite. Replaces #111 stencil and is recommended for deep media blast etching of glass.

PRODUCT APPLICATION

Design centers must be taped before transferring rubber to substrate.

STANDARD SIZES

19.875" x 10 yards
24" x 10 yards

STORAGE & SHELF LIFE

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended. Shelf life is 12 months from date of manufacture.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/20

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive	Medium Tack / Rubber
Total Thickness (mil) PSTC-133	39 (0.99mm)
Total Thickness w/o Liner (mil) PSTC-133	33 (0.84mm)
Tensile Strength (lbs/in) PSTC-131	4 (17.5 N/25mm)
180° Adhesion to Steel (oz/in) PSTC-101	23 (6.3 N/25mm)
Elongation (% at break) PSTC-131	250
Punch	Unpunched, Hand Cut
Liner Color	Clear
Recommended Filler	#211



ANCHOR
brand stencil products