



Technical Data Sheet

Page 1 of 1

Properties: AKEMI® Mildew Remover is a fast-acting, slightly alkaline cleaning

agent based on active chlorine compounds. The product is free of

solvents.

Application Area: AKEMI® Mildew Remover rapidly and thoroughly removes mildew and

mould stains in sanitary areas on cement- and silicone joints, tiles and plastic parts as well as on natural stone, masonry, plaster or other

mineral surfaces.

Instructions for Use: 1. Evenly spray from a distance from approx. 25 cm.

2. Do not let dry. Repeat if necessary.

3. Allow to work for 10-20 minutes, thoroughly clean with water and a

brush made of synthetic material.

4. Repeat cleaning in case of stubborn dirt.

Special Notes: - The product is registered by Bundesanstalt für Arbeitsschutz und

Arbeitsmedizin (BAuA) under the no. N-38700 and by

Bundesinstitut für Risikobewertung (BfR) under the no. 2036171.

- Wear suitable protective gloves.

- Do not allow contact with plants, otherwise wash with plenty of

water.

- Do not allow contact with metal, wood, clothing or similar to avoid discolouring or bleaching. If in doubt try at an inconspicuous area.

- Do not refill used material in the original container.

Protect against direct sunlight and heat.

The spray cap of the spray bottle should be removed after use,

cleaned with water and replaced by the original closure.

For proper waste disposal, the container must be completely

emptied.

Recycling in accordance with the guidelines of EU Decision 97/129

EC on the Packaging Directive 94/62/EC.

Technical Data: Coverage: approx. 10 - 20 m²/liter

Colour: yellowish transparent Density: approx. 1.10 g/cm³

pH value: approx. 11

Storage: If stored in dry and cool condition (5-25°C/41-77°F) in its closed original

container at least 12 months from production.

Health & Safety: Read Safety Data Sheet before handling or using this product.

Important Notice: The above information is based on the latest stage of development and

application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample

piece.

TDS 01.22